

BOOMERANG SOCCER BALL


February 11, 2002

MAE6263

Charles O'Neill

PROBLEM DEFINITION

The goal is to determine possible Soccer ball launch configurations that result in the ball returning to the launch site.



MATHEMATICAL DESCRIPTIONS

The problem is modeled with Newton's Law in two dimensions applied to a sphere. Drag and buoyancy effects are considered.

$$\frac{d^2x}{dt^2} = \frac{3\rho}{4D} C_D (U_F - u) w_r \left/ \left(1 + \frac{1}{2}\rho\right)\right.$$

$$\frac{d^2y}{dt^2} = \left(-(1-\rho)g + \frac{3\rho}{4D} C_D (U_F - u) w_r \right) \left/ \left(1 + \frac{1}{2}\rho\right)\right.$$




$$C_D = f(\text{Re})$$

SOLUTION TECHNIQUE

Individual trajectories are time marched forward with a Runge Kutta 4th order ODE Solver

Return trajectories are found by iterating launch angles with a half interval search routine.

RESULTS



DISCUSSION

A returning soccer ball is possible with the proper launch angle and velocity. A headwind is required except for the purely vertical case.

Trajectories with long free fall times are extremely sensitive to their initial conditions. These critical trajectories have outgoing and incoming paths that are vastly different.

Flow regimes and the resulting drag coefficients clearly dominate the launch configurations. The transition to fully turbulent flow increases the required launch angle. Higher headwinds quicken the appearance of the turbulent regime. As such, drag modeling is critical.

CONCLUSION

Soccer ball launch configurations for a returning ball exist. Critical influence parameters were identified.